



PRODUCT DATA SHEET

SAFETY SOLVENT Solvent Code:047

SAFETY SOLVENT is a high flash kerosene based solvent for general purpose degreasing and parts washing machines.

CAUTION

SAFETY SOLVENT safety requirements

- Volatile, non flammable with a flash point more than 65 degrees
- Caution should be exercised when used in confined areas
- Working areas should be well ventilated and away from any ignition source
- A breathing mask is advisable to avoid inhaling any vapours

APPLICATIONS

SAFETY SOLVENT is ideal for the removal of oil and grease on engine and transmission parts.

SAFETY SOLVENT has good solvency power and may be applied to the components to be cleaned, left to soak, and then left to air dry or hosed off .

SAFETY SOLVENT has a flash point above 65 degrees therefore is recommended for use in power washers and parts washers.

SAFETY SOLVENT will not affect painted surfaces unless prolonged contact occurs which may cause some softening of the paint.

SAFETY SOLVENT is colourless with a low odour and dries with a light residual film.

TYPICAL MAIN CHARACTERISTICS

Flash Point C	64 C
U.N. Number	N/A
Hazchem Code	N/A
DG Class/ Sub Risk	N/A
Poisons Schedule	S5
AS 1940 Class	C1

PACKAGE SIZE 20 & 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary to manufacturing tolerances