



PRODUCT DATA SHEET

FAST DRYING SOLVENT Solvent

Code:048

FAST DRYING SOLVENT is a fast drying solvent for general purpose degreasing, without leaving a film.

CAUTION - FLAMMABLE

FAST DRYING SOLVENT safety requirements

- Highly volatile and flammable with flash point of less than 0 degrees
- Caution should be exercised when using in confined areas
- Working areas should be well ventilated and away from any ignition source
- A respirator or breathing mask is advisable to avoid inhaling any vapours

APPLICATIONS

FAST DRYING SOLVENT will remove oil and grease on engine and transmission parts.

FAST DRYING SOLVENT has high solvency power and may be applied to the components to be cleaned, left to soak, then left to air dry.

FAST DRYING SOLVENT is colourless with low odour and dries without leaving any residual film.

FAST DRYING SOLVENT will affect painted surfaces and should not be used where contact with painted surfaces is likely to occur.

FAST DRYING SOLVENT is harmless to all metals and concrete surfaces.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Flash Point C	-30 C
U.N. Number	1268
Hazchem Code	3 [Y] E
DG Class / Sub Risk	3 / N/A
Poisons Schedule	5
AS 1940 Class	3
PG	II
PACKAGE SIZE	20 & 200 Litres

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.