



# PRODUCT DATA SHEET

## 4 STROKE Automotive Engine Oil

SAE 30 SF/CC

Code:113

**4 STROKE** is a monograde SAE 30 oil for use in petrol and diesel engines which are naturally aspirated operating as stationary engines and in off road mobile equipment.

### SPECIFICATIONS

**4 STROKE** meets or exceeds the following specifications.

- API SF/CC
- US MILITARY - MIL -L- 46152C
- SAE 30
- CCMCG2

### APPLICATIONS

**4 STROKE** is suitable for the lubrication of all types of small engines such as Briggs and Stratton, Yamaha and Honda. Often used in farm equipment, golf course maintenance equipment and by professional tradesman requiring off-site power generation or pumping services.

**4 STROKE** is suited for equipment such as, small electric generators, pumps, and low ride-on lawn mowing machinery.

**4 STROKE** is suitable for small diesel engines where API CC diesel rating is required and is coloured red and has a low phosphorous content which protects the life of catalytic converters and its low ash content assists in preventing diesel injector fouling.

**4 STROKE** provides a high level of protection against wear, sludge formation and acid corrosion and assists in maintaining engine cleanliness and extending the life of moving parts subject to wear.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE 30
Specific gravity at 15 c	0.87
Viscosity at 40c, mm <sup>2</sup> /s (cSt)	95
Viscosity 100c, mm <sup>2</sup> /s (cSt)	10.5
Viscosity index	109
TBN, mgKOH/g	5.8
Flash Point C	227

**PACKAGE SIZE** 1, 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.