



PRODUCT DATA SHEET

HI-VIS 50 Automotive Engine Oil

SAE 50 SG/CD

Code:115

HI-VIS 50 is a specially blended high viscosity engine oil containing detergent additives, corrosion inhibitors, anti-oxidants and anti-wear agents.

SPECIFICATIONS

HI-VIS 50 meets or exceeds the following specifications.

- API SG/CD
- SAE 50
- CCMC G1, G2, D1

APPLICATIONS

HI-VIS 50 is suitable for use in older vehicles that specify an SG rated oil. This incorporates those operating on L.P.G.

HI VIS 50 has exceptional viscosity characteristics and makes it very suitable for engines with low oil pressure and/or high oil consumption.

HI VIS 50 will also help to reduce engine noise caused by worn parts and is ideally suited for use in 4 stroke motor cycle engines.

HI-VIS 50 is also suitable for use in diesel engines requiring A.P.I. CD performance.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE 50
Specific gravity at 15 c	0.88
Viscosity at 40c, mm ² /s (cSt)	236
Viscosity 100c, mm ² /s (cSt)	24.5
Viscosity index	130
TBN, mgKOH/g	5.8
Flash Point C	227

PACKAGE SIZE 5 & 20 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.