



# PRODUCT DATA SHEET

## AGRILUBE Diesel Engine Oil

20W40 CF4/SG

Code:170

**AGRILUBE** is a Super Tractor Oil Universal (S.T.O.U.) designed to lubricate all systems of the farm tractor.

### SPECIFICATIONS

**AGRILUBE** meets or exceeds the following specifications.

- API CF4/SG
- CCMC D3/G3
- US MILITARY MIL-L-2104D, 46152D
- API GL4
- CATERPILLAR TO-2
- FORD/NEW HOLLAND M2C159A, M2C159B
- SAE 20W40
- CASE JIC 185 & MS 1206
- JOHN DEERE HYGUARD J20C, JD27A
- ALLISON C4
- DAIMLER BENZ DB 227.1
- MACK EOK-2
- MASSEY FERGUSON MF1139, MF1144

### APPLICATIONS

**AGRILUBE** being a truly "Universal" oil, is suitable for engines, transmissions, hydraulic systems, final drives, wet brakes, power take offs, hydrostatics and power steering systems in farm tractors and other implements.

**AGRILUBE** is blended basically as an engine oil and contains special frictional additives to satisfy hydraulic and wet brake applications.

**AGRILUBE** is also suitable for all petrol and diesel engines where API CF4/SG is specified.

**AGRILUBE** has a low phosphorus level, there by meeting the requirements of the Australian passenger car manufacturers.

**AGRILUBE** has the highest level of performance in gear and anti-squawk characteristics.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	20W40
Specific gravity at 15 c	0.889
Viscosity at 40c, mm <sup>2</sup> /s (cSt)	118
Viscosity 100c, mm <sup>2</sup> /s (cSt)	13.2
Viscosity index	107
TBN, mgKOH/g	8
Flash Point C	215
Sulphated ash %	1.4
<b>PACKAGE SIZE</b>	5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.