



PRODUCT DATA SHEET

M1 SPECIAL

Semi-Synthetic Automotive Engine Oil

10W40 SL/CF

Code:201

M1 SPECIAL is a semi-synthetic oil which provides better protection from piston deposits, less oil thickening and sludge deposits and exceptional anti-wear protection under high speed and high stress.

SPECIFICATIONS

M1 SPECIAL meets or exceeds the following specifications.

- API SL/CF
- ACEA A3/B3/B4
- DAIMLER BENZ DB 229.1
- SAE 10W40
- VW 500.00 / 505.00

APPLICATIONS

M1 SPECIAL is suitable for all late model petrol engine vehicles including those fitted with turbo chargers. Ideal for use in L.P.G fuelled vehicles and diesel engines where API CF performance or better is stipulated.

M1 SPECIAL meets or exceeds the requirements of an SL/CF engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion.

M1 SPECIAL assists in maintaining engine cleanliness and additionally assists in energy conservation and fuel economy.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W40
Specific gravity at 15 c	0.88
Viscosity at 40c, mm ² /s (cSt)	100
Viscosity 100c, mm ² /s (cSt)	14
Viscosity index	142
TBN, mgKOH/g	9.1
Flash Point C	227

PACKAGE SIZE 1, 6.5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.