

PRODUCT DATA SHEET

AUTOSYN LO-VISSynthetic Transmission Fluid

Code:213

AUTOSYN LO-VIS is synthetic, low viscosity automatic transmission fluid designed to meet specific manufacturers specifications.

• FORD NGF (Next Generation Factory Fill), M2C-919-D, LV

SPECIFICATIONS

AUTOSYN LO-VIS meets or exceeds the following performance specifications.

MERCON SP
MB NAG-2

TOYOTA WS

DEXRON VI

APPLICATIONS

AUTOSYN LO-VIS is blended with synthetic base oil combined with superior additive technology to produce a product that provides exceptional low viscosity and improved low temperature performance along with shear and friction stability.

AUTOSYN LO-VIS is premium service fill automatic transmission fluid suitable for late model and imported vehicles.

AUTOSYN LO-VIS is specially formulated to meet new generation vehicle technology.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Specific gravity at 15 C	0.866
Viscosity at 40 C, mm2/s (cSt)	30
Viscosity at 100 C, mm2/s (cSt)	6
Flash Point C	213
Pour Point deg c	<-30
Viscosity Index	151

PACKAGE SIZE 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.