



PRODUCT DATA SHEET

TRANSGEAR 75W 90 Synthetic Gear Oil

GL5
Code:216

TRANSGEAR 75W90 is a multi grade lubricant manufactured from synthetic base oil with extreme pressure and limited slip additives to impart friction reducing and energy conserving properties.

SPECIFICATIONS

TRANSGEAR 75W90 meets or exceeds the following specifications.

- API GL5, MT-1
- SAE 75W90
- MILITARY SPECIFICATIONS MIL-PRF-2105E
- GENERAL MOTORS HN-1561, HN-2040
- FORD ESZ M2C-190A, MC20119 A, MC2-104
- MACK GO-J
- SAE J2360

APPLICATIONS

TRANSGEAR 75W90 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions and also where high performance limited slip applications are required.

TRANSGEAR 75W90 offers energy conservation, improved transmission life, easy gear shifting and less maintenance these are the main benefits associated with this product.

TRANSGEAR 75W90 will provide maximum protection to gearboxes and differentials used in modern trucks and four wheel drives towing caravans and boats and is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions where heat and load are major factors.

TRANSGEAR 75W140 is suitable for Limited Slip Differentials in all vehicles.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	75W90
Specific gravity at 15 c	0.88
Viscosity at 40c, mm ² /s (cSt)	115
Viscosity 100c, mm ² /s (cSt)	16.5
Viscosity index	165
Flash Point C	213

PACKAGE SIZE 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.