



PRODUCT DATA SHEET

VACUUM PUMP 68 Industrial Lubricant

ISO 68
Code:312

VACUUM PUMP 68 is a premium vacuum pump lubricant formulated from solvent refined, highly stable base stocks.

SPECIFICATIONS

VACUUM PUMP 68 meets or exceeds the following specifications.

- ISO 68

APPLICATIONS

VACUUM PUMP 68 is suitable for all milking machine vacuum pumps except Westfalia models.

VACUUM PUMP 68 results in longer valve cleaning intervals as a result of high resistance to deposit formation and outstanding oxidation stability.

VACUUM PUMP 68 will reduce component wear as a result of excellent rust protection and high film strength and result is a finished product which is minimum deposit forming, has long life, protects pump components from wear and also separates readily from water.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ISO 68
Viscosity at 40 C, (cSt)	68
Viscosity at 100 C,(cSt)	7.8
Density	0.87
Viscosity Index	108
Flash Point deg C	223
Pour Point deg C	-28
Copper Corrosion ASTM D130	1b

PACKAGE SIZE 20 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.