



# PRODUCT DATA SHEET

## BRICK/MOULD RELEASE Industrial Lubricant

ISO 22  
Code:322

**BRICK/MOULD RELEASE** is a fortified fluid with excellent surface conditioning characteristics to enable quick release of the mould and impart an excellent surface finish.

### SPECIFICATIONS

**BRICK/MOULD RELEASE** meets or exceeds the following specifications.

- ISO 22

### APPLICATIONS

**BRICK/MOULD RELEASE** is suitable for all types of moulds and formwork where concrete, plaster or clay brick, tile or paver products are being manufactured.

**BRICK/MOULD RELEASE** will adhere to the steel mould and prevent surface corrosion which might discolour the product finish or create defects in the product surface.

**BRICK/MOULD RELEASE** may be extended with high flash kerosene to give the desired result in clay pipe extrusion machines.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ISO 22
Viscosity at 40 C, (cSt)	18.5-21.0
Viscosity at 100 C,(cSt)	4.3
Flash Point deg C	200
Pour Point C	-10

**PACKAGE SIZE** 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.