

**SLIDEWAY  
Industrial Lubricant**

Code:348, 350, 350,351, 352

**SLIDEWAY OIL** is a mineral base lubricant formulated with selected extreme pressure additives and special additives for tackiness and adhesiveness.

**SPECIFICATIONS**

**SLIDEWAY** meets or exceeds the following specifications.

- ISO 32, 68, 150 & 220

**APPLICATIONS**

**SLIDEWAY OIL** protects saw blades and guides from abrasive wear and can be applied manually or in automatic lubrication systems.

**SLIDEWAY OIL** is a tacky extreme pressure and anti-wear lubricant with excellent cling characteristics that resists throw off, water wash off and corrosion under high and low speeds.

**SLIDEWAY OIL** will assist in increasing equipment life.

**SLIDEWAY OIL** is ideal for lubricating manufacturing machinery under high loads and pressures such as in lathes, milling machines and other equipment with slides and carriage ways.

**SLIDEWAY OIL** will adhere to the working surfaces under high load and temperature and resist wash out from water soluble cutting fluids.

**TYPICAL MAIN CHARACTERISTICS**

<b>CHARACTERISTICS</b>	<b>ISO 32</b>	<b>ISO 68</b>	<b>ISO 150</b>	<b>ISO 220</b>
Viscosity @ 40 C cSt	32	68	150	220
Viscosity @ 100 C cSt	6	7.7	13.6	19
Viscosity Index	105	105	105	97
Flashpoint	203	205	205	205
Density	0.86	0.87	0.88	0.9

**PACKAGE SIZE** 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.