



# PRODUCT DATA SHEET

## AUTO TRANS FLUID DXR III Semi-Synthetic Transmission Fluid

Code:401

**AUTO TRANS FLUID DXR III** is a semi-synthetic premium quality fluid blended to meet Dexron 111 H specifications.

### SPECIFICATIONS

**AUTO TRANS FLUID DXR 111** meets or exceeds the following specifications.

- GENERAL MOTORS- DEXRON III H, II
- ALLISON C4
- SPERRY VICKERS HYDRAULIC PUMP SYSTEMS
- DENISON HYDRAULIC PUMP SYSTEMS
- FORD MERCON
- CATERPILLAR TO-2
- SUNSTRAND HYDRAULIC PUMP SYSTEMS
- ZF: TE-ML 05L/09

### APPLICATIONS

**AUTO TRANS DXR 111** is a high viscosity index fluid containing superior additive technology which provides exceptional thermal stability as well as oxidation resistance and sludge control.

**AUTO TRANS FLUID DXR III** should be used wherever Dexron 111 is specified and is suitable for all General Motors four speed automatic transmissions.

**AUTO TRANS FLUID DXR 111** may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

**AUTO TRANS FLUID DXR 111** is also approved for use where Allison C4 fluid is recommended.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W30, 80W
Specific gravity at 15 C	0.866
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	34
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	7.1
Viscosity index	170
Flash Point Degree C	210
Pour Point Deg C	<42
Colour	Red

**PACKAGE SIZE** 1, 5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.