



PRODUCT DATA SHEET

GEAR OIL 85W140

Gear oil

GL5

Code:410

GEAR OIL 85W140 is a multigrade lubricant containing sophisticated extreme pressure additives.

SPECIFICATIONS

GEAR OIL 85W140 meets or exceeds the following specifications.

- API GL5, MT-1
- MILITARY SPECIFICATIONS MIL-L-2105D
- SAE 85W140
- FORD-M2C108-A, M2C105-A
- MACK GO - J
- GENERAL MOTORS HN-1187, HN-1386
- BORG WARNER 5M-26

APPLICATIONS

GEAR OIL 85W140 is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions.

GEAR OIL 85W140 will provide maximum protection when subjected to severe shock loads, exceptional oxidation stability during high ambient temperatures and outstanding corrosion protection and anti-foam additives protect gear box and differential components.

GEAR OIL 85W140 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this type of gear oil.

GEAR OIL 85W140 is suited for trucks, heavy agriculture machinery, earthmoving and excavating equipment.

GEAR OIL 85W140 may be a suitable for 80W90 specifications where high temperatures are encountered.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	85W140
Specific gravity at 15 c	0.89
Viscosity at 40c, mm ² /s (cSt)	320
Viscosity 100c, mm ² /s (cSt)	25
Viscosity index	100
Flash Point C	227

PACKAGE SIZE 4, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.