



# PRODUCT DATA SHEET

## GEAR OIL 75W90 GL-5

Code:414

**GEAR OIL 75W90** is a multigrade lubricant containing sophisticated extreme pressure additives. Gear Oil is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions.

### SPECIFICATIONS

GEAR OIL 75W90 meets or exceeds the following specifications.

- API- GL5
- 75W90
- MACK GO - J
- BORG WARNER 5M-26
- MILITARY SPECIFICATIONS MIL-L-2105D
- GENERAL MOORS HN-1187,HN-1386
- FORD-M2C108-A, M2C105-A
- DAIMLER-BENZ 235/2F

### APPLICATIONS

GEAR OIL 75W90 is recommended for use in manual transaxles in incorporating hypoid gears. The main applications for this product are manual transaxles fitted to selected late model European passenger cars. Additionally this product can be used where gear shift problems are encountered to allow for easier gear operation.

Using this product will provide the following benefits:

Maximum protection when subjected to severe shock loads.  
Exceptional oxidation stability during high ambient temperatures.  
Outstanding corrosion protection and anti-foam additives protect gear box and differential components.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	75W90
Specific gravity at 15 c	0.869
Viscosity at 40c, mm <sup>2</sup> /s (cSt)	100
Viscosity 100c, mm <sup>2</sup> /s (cSt)	15
Viscosity index	157
Flash Point C	227

**PACKAGE SIZE** 4 Litre, 20 Litre, 60 Litre & 20 Litre & 20 205

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.