



# PRODUCT DATA SHEET

## GEAR OIL LIMITED SLIP 90 Gear Oil

GL5  
Code:420

**GEAR OIL LIMITED SLIP 90** is a high performance gear lubricant containing extreme pressure additives and special friction modifiers for limited slip differentials.

### SPECIFICATIONS

**GEAR OIL LIMITED SLIP 90** meets or exceeds the following specifications.

- API GL5
- GENERAL MOTORS- HN-1386, HN-1561, HN-1187
- SAE 90
- MILITARY SPECIFICATIONS MIL-PRF-2105E
- BORG WARNER-5M-31
- FORD- M2C104-A, M2C105-A, M2C119-A, M2C1006-A, M2C1006B

### APPLICATIONS

**GEAR OIL LIMITED SLIP 90** has been developed for cars and commercial vehicles fitted with limited slip differentials.

**GEAR OIL LIMITED SLIP 90** is primarily used for differentials in numerous vehicles and particular suited for tractor and construction equipment requiring a gear oil lubricant of SAE 90 viscosity.

**GEAR OIL LIMITED SLIP 90** contains sophisticated extreme pressure additives providing excellent wear protection in vehicles operating under severe stress and high temperatures.

**GEAR OIL LIMITED SLIP 90** may also be used as a high performance substitute for SAE 90 grade oil when used in hypoid and spiral bevel gears.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE 90
Specific gravity at 15 c	0.866
Viscosity at 40c, mm <sup>2</sup> /s (cSt)	202
Viscosity 100c, mm <sup>2</sup> /s (cSt)	17.5
Viscosity index	106
Flash Point C	203

**PACKAGE SIZE** 1, 4, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.