



PRODUCT DATA SHEET

A.F.A.B. 50 PREMIX Cooling System

TYPE A
Code:500B

A.F.A.B. 50 PREMIX is a premixed mono ethylene glycol based coolant containing an advanced inhibitor system to protect cooling systems from corrosion and scale formation.

SPECIFICATIONS

A.F.A.B. 50 PREMIX meets or exceeds the following specifications.

- AS/NZS 2108 - 1997 TYPE A
- GENERAL MOTORS GM- 1825M & GM -1899M
- DETROIT DIESEL 7SE298
- AS 2108-84
- GENERAL MOTORS GM - 6043
- NISSAN NES 5059 LLC
- FORD ESE-M97B44-A
- GMH HN - 2043 (50% v/v water solution)
- CATERPILLAR 1 EO 535
- FORD ESE-F97B18-C
- CUMMINS 92T8-9

APPLICATIONS

A.F.A.B. 50 PREMIX is for use in conventional engines with a mixture of aluminium and cast iron as well as high performance diesels and especially suited for vehicles fitted with air conditioning.

A.F.A.B. 50 PREMIX will give protection to engine cooling systems for 3 years or 100,000 kilometres based on normal operating conditions.

A.F.A.B. 50 PREMIX is a powerful, nitrite, amine, phosphate and silicate free coolant.

DIRECTIONS FOR USE:

Drain out and thoroughly flush the engine cooling system and heater circuit. Completely fill the cooling system with A.F.A.B. 50 PREMIX as this product contains 45% Antifreeze Antiboil and 55% deionised water.

Do not add water to the system or to this product. It is premixed and ready to use.

POISON: THIS PRODUCT IS HARMFUL, IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	A.F.A.B. 50
Appearance	Fluorescent Green
Odour	Mild
Specific gravity at 15 C	1.06 Typical
pH (50% water)	10.3 -10.7
Ethylene Glycol	45%
Freezing Point (Type A less than -12oC)	50% v/v Solution <34 C

PACKAGE SIZE 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.