



PRODUCT DATA SHEET

SUPER 2 STROKE

Specialty Product

API TC

Code:510

SUPER 2 STROKE is a low ash high performance two stroke engine oil for use in non outboard applications.

SPECIFICATIONS

SUPER 2 STROKE meets or exceeds the following specifications.

- API TA/TB/TC
- JASO FB/FC
- ISO EGD

APPLICATIONS

SUPER 2 STROKE is a self-mixing oil, formulated with a special solvent to disperse quickly and readily throughout the fuel in the fuel tank and is suitable for oil injection systems often fitted to modern two stroke engines.

SUPER 2 STROKE provides protection from piston and exhaust port deposits, spark plug fouling and exceptional anti-scuff protection.

SUPER 2 STROKE assists in maintaining engine cleanliness in all air cooled two stroke engines.

RECOMMENDED TREAT RATE:

SUPER 2 STROKE should be mixed with petrol in the ratios recommended by the engine manufacturer. In the absence of any information from the manufacturer, 30 to 1 fuel/oil would be an advisable starting point and may be leaned out to 50 to 1 as experience dictates.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	JASO FB/FC
Specific gravity at 15 c	0.856
Viscosity at 40c, mm ² /s (cSt)	63
Viscosity 100c, mm ² /s (cSt)	7 Typical
Viscosity index	106
Flash Point C	90 Typical
Sulphated ash	0.28

PACKAGE SIZE 1, 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.