



PRODUCT DATA SHEET

MULTIPURPOSE Grease

NLGI 2
Code:600

MULTIPURPOSE GREASE is a lithium based grease with a slightly stringy texture recommended for automotive, marine and industrial applications.

SPECIFICATIONS

MULTIPURPOSE GREASE meets or exceeds the following specifications.

- NLGI 2

APPLICATIONS

MULTIPURPOSE GREASE is recommended for ball, roller, needle and slow speed plain bearings operating under all service conditions.

MULTIPURPOSE GREASE contains extreme pressure additives to cater for automotive chassis applications, earth moving, truck trailers, farm and industrial equipment.

MULTIPURPOSE GREASE possesses excellent lubrication characteristics for bearings operating under normal or severely loaded conditions and is fortified with rust, oxidation and corrosion inhibitors with shear stabilisers.

MULTIPURPOSE GREASE will protect all moving parts from scuffing, shock loadings, water wash-out, oxidation under high temperatures applications and extend service life of the grease.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	NLGI 2		
Penetration @ 25 deg C Worked 60 strokes	275	Timken OK Load kq	23
Worked 1000 strokes	292	Mineral Oil Viscosity @ 40 C cSt	314
Dropping point (deg c	192	Mineral Oil Viscosity @ 100 C cSt	19.2
Water Washout @ 80 deg C %	5	Rust Prevention	No Rust
Wheel Bearing Leakage (e gm	3	Maximum Usable Temperature C	140
		Lithium Soap % mass	9.2

PACKAGE SIZE 450 Gm, 2.5, 20, 55 & 180 Kgs

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.