



PRODUCT DATA SHEET

RADIATOR FLUSH Stop It Additive

Code:717

RADIATOR FLUSH is a powerful de-scaling agent to safely remove and suspend deposits that form in the cooling system that cause overheating and corrosion.

SPECIFICATIONS

RADIATOR FLUSH meets or exceeds the following specifications.

- N/A

APPLICATIONS

RADIATOR FLUSH can be use in all types of cooling systems where there are aluminium alloy, copper, brass or cast iron present.

RADIATOR FLUSH is recommended for high performance, petrol, diesel and L.P.G fuelled engines.

DIRECTIONS:

Empty the cooling system of all coolant and refill with clean water.

Add 350 mil to a 10 litre or less system capacity and run the engine at idle speed for 20 minutes, in very dirty systems increase the run time to 60 minutes.

Flush out the cooling system with clean water and refill with fresh coolant to manufactures specifications.

If heavily contaminated with sludge and oil, repeat steps.

HARMFUL, KEEP OUT OF REACH OF CHILDREN, DO NOT SWALLOW, DO NOT INDUCE VOMITING IF LESS THAN 15 MINUTES FROM A HOSPITAL, STRONG ALKALINE SO AVOID CONTACT WITH SKIN AND EYES, IF IN EYES HOLD EYE LIDS APART AND FLUSH WITH RUNNING WATER FOR 15 MINUTES, IF SKIN IS CONTACTED REMOVE CLOTHING AND RINSE WITH WATER, SEEK MEDICAL ADVICE IMMEDIATELY.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Appearance	Slimy hazy liquid
Specific Gravity	1.3 Typical
pH Value	12 Typical

PACKAGE SIZE 350 Mil

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.